Set Name Query ide by side		Hit Count Set Name result set	
DB=US	SPT; PLUR=YES; OP=ADJ		
<u>L18</u>	(L1 or L9) and L17	1	<u>L18</u>
<u>L17</u>	718/103.ccls.	508	L17
<u>L.16</u>	(L1 or L9) and L15	4	<u>L16</u>
<u>L15</u>	719/313-314.ccls.	566	<u>L15</u>
L14	(L1 or L9) and L12	1	<u>L14</u>
L13	(L1 or L9) and L11	1	<u>L13</u>
<u>L12</u>	709/240-241.ccls.	501	<u>L12</u>
<u>L11</u>	709/206-207.ccls.	2042	LH
<u>L 10</u>	L9 same message	3	L10
<u>L9</u>	block\$ with semaphore with application	28	L9
<u>L.8</u>	L1.clm.	1	<u>L8</u>
<u>L7</u>	L1 and wak\$	4	<u>L7</u>
<u>L6</u>	L1 same wak\$	0	<u>L6</u>
<u>L5</u>	message classes same semaphore	0	<u>L5</u>
<u>L4</u>	message classes same application same semaphore	0	<u>L4</u>
<u>L3</u>	L1 same block\$	4	<u>L3</u>
<u>L2</u>	L1 same classes	4	<u>L2</u>
<u>L1</u>	state same application same semaphore same message	47	<u>L1</u>

## END OF SEARCH HISTORY

Set Name Query ide by side		Hit Count Set Name result set		
DB=PGPB; $PLUR=YES$ ; $OP=ADJ$				
<u>1.13</u>	(L1 or L4) and L9	0	<u>L13</u>	
<u>L12</u>	(L1 or L4) and L8	4	<u>L12</u>	
<u>1.11</u>	(L1 or L4) and L7	0	<u>L11</u>	
<u>1.10</u>	(L1 or L4) and L6	2	<u>L10</u>	
L9	718/103.ccls.	108	<u>L9</u>	
<u>L8</u>	719/313-314.ccls.	304	<u>1.8</u>	
<u>L.7</u>	709/240-241.ccls.	182	<u>L7</u>	
1.6	709/206-207.ccls.	3316	<u>L6</u>	
<u>L5</u>	L4 same message	2	<u>L5</u>	
<u>L4</u>	block\$ with semaphore with application	13	<u>L4</u>	
<u>L3</u>	L1 same block\$	6	<u>L3</u>	
<u>L2</u>	L1 same classes	4	<u>L2</u>	
<u>L1</u>	application same semaphore same message	97	<u>L1</u>	

END OF SEARCH HISTORY